



systems without thermal insulation

Ideal

- _ industrial-style internal aluminium installation system without thermal insulation
- _ Ideal is a door and internal wall system available in many options:
 - single door
 - double door
 - pivot door
 - it is possible to install permanent glazing around the Ideal doors with top and/or side light; depending on the demand and the style of the interior, a permanent wall solution is also available, with or without astragal bars
- _ the IDEAL system is based on a 33 mm thin profile allowing the creation of structures that fit into modern loft design
- _ the IDEAL glazing system is an alternative to the classic partition walls that separate rooms
- _ both the doors and walls of the Ideal system can have different dividing patterns, enabling them to be perfectly tailored to the interior design. The Ideal system is characterised by versatility and functionality
- _ in order to maintain structural uniformity, the Ideal system has specially designed grips and matching handles and escutcheons; available types:
 - handle
 - grips
 - escutcheon (cylinder lock / key lock / bolt lock)
- _ wide range of colours – RAL palette (Qualicoat 1518), textured colours, Aliplast Wood Colour Effect – wood-like colours, Aliplast Loft View – colours imitating stone surfaces (Qualideco PL-0001), anodised colour (Qualanod 1808), bi-colour



systems without thermal insulation

technical specification

system	material	visible width	visible width of the door light	glazing	maximum width of the structure	hinges
ID	aluminium / polyamide	starting from 33 mm	40 mm	8-10-12 mm	2000 cm	visible or concealed (adjustable)

