

Transmittance **$U_w \geq 1.3$ (W/m²K)**

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing	30 mm
Minimum glazing	26 mm
Maximum acoustic insulation	Rw = 41 dB

Sightlines

Frame	116 mm
	182 mm 3 rails
Sash	37 mm

Profile Thickness

Door	1.7 mm
------	--------

Polyamide strip length 16 - 24 mm**Maximum dimensions / Sash**

Width (L) = 2,500 mm

Height (H) = 3,000 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash 320 kg**Categories achieved at test centre**

Protection against atmospheric agents.

Air permeability**(UNE-EN 12207): Class 4****Water tightness****(UNE-EN 12208): Class 7A****Wind resistance****(UNE-EN 12210): Class C5**

* Reference test 1.23 x 1.55 m / 1 sash + 1 fixed light

Security test: **PAS24** ☒

Passed

Test verified by

ALUMINIOS CORTIZO S.A.U.**Extrusion alloy**

6063 T-5

Finishes

Possibility of dual colour.

Colour powder coating (RAL, mottled & rough).

According to Qualicoat >60 microns

Wood effect powder coating.

According to Qualideco standard

Anodised.

According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Sliding with 1, 2, 3, 4 & 6 sashes

Possibility of 1, 2 or 3 rails

Possibility of inner and outer corner sash at 90° without a mullion

Pocket sliding door of 1, 2, 3, 4 & 6 sashes

